

B-250

Stick Welding
Power Source

Quick Specs

Industrial Applications
Petro/Chem Fabrication
Shipboard Installation/Repair
Mechanical Contractors
Mining
Process Piping

Power Voltage
1 Phase AC240V ±15%

Input Current
29A/7kVA

Output Current
30-200A
Max. OCV: 66VDC
Output Voltage
30.8V

Duty Cycle
70%

Weight
10KG

Dimensions
D425×H355×W205MM

Portable. Professional. Rugged. Affordable.

The inverter B-250 offers much more than you would expect from a welder this size. Weighing in at just under 10kg the Inverter B-250 is no lightweight contender. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It can operate from a portable generator.

FEATURES

- **Arc Force** minimizes electrode sticking in the puddle without compromising arc stability or increased spatter.
- **Automatic Hot Start** boosts the current during starting to make striking an arc easier.
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- Inverter-based, DC power source has a **simple-to-use operator interface** providing only the necessary controls in a compact machine.



PROCESSES

Stick (SMAW)
DC TIG (GTAW)

INCLUDED

B-250 Machine Only Includes:

- B-250
- 2PCS 35MM² MALE PLUG

INPUT



OUTPUT



AUSTCORP MANUFACTURING SDN. BHD.
NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3
TAMAN BATU GAJAH PERDANA
31550 PUSING PERAK MALAYSIA
TEL: (605)3632 115 FAX: (605)3632 111
E-mail: austcorp@welding.com.my
WEB: www.welding.com.my



Welding Technology