

DC PULSE TIG/MMA

VT-315P

TIG Welding
Power Source

Quick Specs

Light Industrial Applications

Maintenance Repair
Shipboard Installation
Fabrication
Hobbyist
Process Piping

Power Voltage

3 Phase AC415V ±15%
50/60Hz

Input Current

12.5A/9kVA

Output Current

3-315A
Max. OCV: 70VDC

Output Voltage

10V~22.6V

Duty Cycle

60%

Weight

18.5KG

Dimensions

D530×H370×W215MM

Portable. Professional. Rugged. Affordable.

The inverter **VT-315P** offers much more than you would expect from a welder this size. Weighing in at just under 18.5kg the Inverter **VT-3 15P** is no lightweight contender. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It can operate from a portable generator.

FEATURES

- DC inverter for TIG with advanced inverter technology to optimize arc performance.
- Improved TIG Starting. Now starts DC(-) to maintain a sharp tungsten.
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- 315 amps @ 60% duty cycle is the highest output rating in this machine class.
- Inverter-based, DC power source has a **simple-to-use operator interface** providing only the necessary controls in a compact machine.
- **Built-in pulsing functions** 0.5~300Hz

PROCESSES

DC TIG (GTAW)
MMA

INCLUDED

VT-315P Machine Only Includes:

- VT-315P
- 7M WP26F-2 TIG TORCH.
- 3M work cable and clamp.

INPUT



OUTPUT



AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3
TAMAN BATU GAJAH PERDANA
31550 PUSING PERAK MALAYSIA
TEL: (605)3632 115 FAX: (605)3632 111
E-mail: austcorp@welding.com.my
WEB: www.welding.com.my



Welding Technology